



1701 Hollow Metal Door with Polystyrene Core Bullet Resistant UL 752 Level 1

| | |
|--------------------|---|
| Face Material | Galvannealed A40 or A60 ASTM-A-653 |
| Face thickness | 12 Ga. (.0994 min thickness) CS type B |
| Construction | Rigid polystyrene core bonded to both face sheets |
| Door thickness | 1 3/4" Standard |
| Hardware Locations | Any specified locations. Door hardware Certified and Listed for UL752 Level 1 application |
| Reinforcements | 7 Ga. 1 1/4" x 10" joggled hinge reinforcement, drilled and tapped 12 Ga. mortise hardware tabs, drilled and tapped 14 Ga. surface hardware and trim reinforcement, drilled and tapped |
| Edge reinforcement | Both edges reinforced with 16 Ga. full length channels spot welded to the face sheets |
| Vertical edges | Fully welded with no visible seam (for doors up to 4' wide and 8' height) |
| Glazing | Glazing and Glazing Frame shall be listed for UL 752, Level 1 (Size per listing, minimum 12 x 12 in). Note: Glass should be cut 1/4" less than door cut out. Exposed glass opening is 1 5/16" less than cutout dimensions. |
| Handing | Doors are handed |
| Appearance | Faces and edges free of defects, warp and buckle |
| Finish | Thoroughly cleaned and coated with a rust inhibiting primer meeting |

